

## NOTES:

- 1. CONTRACTOR SHALL SUPPLY SUBMITTAL TO THE CITY OF GERMANTOWN FOR ACCEPTANCE. THE CITY WILL BE RESPONSIBLE TO DETERMINE WHETHER IT IS EQUAL TO OR MEETS PROJECT SPECIFICATIONS.
- 2. UNLESS OTHERWISE NOTED ON PLANS, CONCRETE SHALL BE CLASS A, 3500 psi READY MIX TYPE CONFORMING TO ASTM SPECIFICATION C94 AND COMPOSED OF PORTLAND CEMENT, SAND, AND WASHED COURSE LIMESTONE AGGREGATE.
- 3. ALL MATERIAL SHALL BE POWDER COATED ALUMINUM.
- 4. ALL PARTS SHALL BE PAINTED WITH TGIC UV RESISTANT SEMIGLOSS BLACK FINISH.
- 5. ALL COMPONENTS REQUIRING WELDING SHALL HAVE A SOLID WELD.
- 6. FOR BOLT HOLE DRILL PATTERN, SEE CITY OF GERMANTOWN 'DECORATIVE STREET POST BOLT PATTERN DETAIL'.



CHECKED:

APPROVED:

## ENGINEERING DEPARTMENT

## DECORATIVE STREET POST

AN	_	(INSTALLATION L	DETAILS)
DRAWN:	MLC	DATE:	07.26.23
CHECKED:	JDB	REVISED:	

EWS

(SHEET 4 of 6)

REVISED: SCALE: NTS