



MINOR STREET TYPICAL SECTION

**NOTES:**

1. ALL SUB-GRADE SHALL BE CONSOLIDATED AND COMPACTED TO NINETY-FIVE (95%) PERCENT STANDARD PROCTOR PER CITY OF GERMANTOWN STANDARD SPECIFICATIONS.
2. ASPHALTIC CONCRETE BASE COURSE SHALL BE TDOT SPECIFICATION 307B or 307C.
3. ASPHALTIC CONCRETE FINAL SURFACE LAYER SHALL BE TDOT SPECIFICATION 411E.
4. ASPHALTIC CONCRETE (BITUMINOUS PLANT MIX) SHALL BE MANUFACTURED IN ACCORDANCE WITH SECTIONS 407 & 411 OF THE TDOT STANDARD SPECIFICATIONS FOR ROAD & BRIDGE CONSTRUCTION.
5. STABILIZED ROAD-BASE SHALL COMPLY WITH THE CITY OF GERMANTOWN STANDARD SPECIFICATIONS SECTION 10, CEMENT STABILIZED AGGREGATE BASE OR SECTION 11, CEMENT STABILIZED SOIL BASE.



ENGINEERING DEPARTMENT

MINOR STREET  
TYPICAL DETAIL

DRAWN: <u>MLC</u>	DATE: <u>06.09.23</u>
CHECKED: <u>JDB</u>	REVISED: _____
APPROVED: <u>EWS</u>	SCALE: <u>NTS</u>