


SECTION A-A

MINOR-STREET VALLEY GUTTER

STEEL REINFORCING/REBAR TABLE			
BAR MARK	SIZE	# REQ'D	LENGTH
501	# 5	4	24'-0"
502	# 5	3	30'-0"
503	# 5	3	25'-0"
504	# 5	2	31'-0"
505	# 5	2	36'-0"
506	# 5	6	7'-6"

NOTES:

1. THE ENTIRE VALLEY GUTTER SHALL BE POURED MONOLITHICALLY. SAW-CUT CONTRACTION JOINTS THE NEXT DAY, AFTER PLACING CONCRETE.
2. CONCRETE THICKNESS SHALL BE SIX (6") INCHES MINIMUM. CONCRETE FINISH SHALL BE A LIGHT-BROOM OR STEEL-TROWEL FINISH. CONCRETE SHALL BE CLASS A, 3500 PSI READY MIX TYPE CONFORMING TO ASTM SPECIFICATION C94 AND COMPOSED OF PORTLAND CEMENT, SAND, AND WASHED COURSE LIMESTONE AGGREGATE.
3. WHEN CONSTRUCTING DIFFERENT RADIUS OF CURB RETURN, THE STEEL LENGTHS WILL CHANGE ACCORDINGLY BUT THE REINFORCING PATTERN SHALL REMAIN THE SAME.
4. INSTALL (2) #5 REBAR DOWEL BARS (24" LENGTH) AT EACH LOCATION SHOWN.
5. TYPICAL VALLEY GUTTER SHALL NOT BE INSTALLED ACROSS MAJOR STREET OR COLLECTOR STREET.



ENGINEERING DEPARTMENT

MINOR-STREET VALLEY GUTTER

DRAWN: MLC

DATE: 07.18.23

CHECKED: JDB

REVISED: _____

APPROVED: EWS

SCALE: NTS