



TYPICAL SEWER SERVICE CONNECTION

NOTES:

1. WHEN PVC IS USED FOR THE SEWER SERVICE LINE CONNECTION, IT SHALL CONFORM TO ASTM D3034, PLASTIC SEWER MAIN TYPE (PSM), POLYVINYL CHLORIDE SEWER PIPE AND FITTINGS WITH A STANDARD DIMENSION RATIO (SDR) OF 26.
2. THE 4" DIAMETER RISER SHALL BE BROUGHT TO GRADE BY PLUMBER AND REPLACED WITH A 4" CLEAN-OUT W/SCREW CAP.
3. A 4" TALL, BLACK STENCILED-PAINTED "S" ON A 6"x6" WHITE BACKGROUND SHALL BE APPLIED TO FACE-OF-CURB AT ALL SEWER SERVICE LINE CROSSINGS.
4. PVC LOCATOR PIPE SHALL BE 2"Ø or 4"Ø PCV PIPE INSTALLED 'PLUMB' AND ADJACENT TO THE 4" RISER. LOCATOR PIPE SHALL EXTEND 2'-0" (MINIMUM) ABOVE FINAL GRADE.



ENGINEERING DEPARTMENT

TYPICAL SEWER SERVICE CONNECTION

DRAWN: <u>MLC</u>	DATE: <u>06.07.23</u>
CHECKED: <u>JDB</u>	REVISED: _____
APPROVED: <u>EWS</u>	SCALE: <u>NTS</u>